

AQUA MULCHER

HYDROSEEDING EQUIPMENT



Paddle Agitation

A thick mulch application is necessary for proper seed germination and plant establishment. Too thin of a mulch slurry results in poor germination and high erosion, especially on steep slopes. The Aqua Mulcher's paddle agitation and positive displacement gear pump allow the user to pump a thick slurry through up to 300' of hose. Spraying distances of up to 75' can be experienced with the Aqua Mulcher. Available options include: extension hose (100' included) up to 300', skid or trailer mounting, as well as a spraying tower and cannon discharge. The Aqua Mulcher is ready to suit all of your needs.



Positive Displacement Gear Pump

Specifications:

	500 Gallon	800 Gallon	1200 Gallon
Length:	95"	115"	132"
Width:	60"	72"	72"
Height:	46"	58"	68"
Height w/ Tower:	66"	66"	74"
Trailer Length:	150"	175"	192"
Trailer Width:	75"	75"	75"
Trailer Height w/ Tower:	58"	78"	87"
Weight (Empty):	1610 lbs	1900 lbs	2,920 lbs
Weight (Working):	6410 lbs	9580 lbs	14,000 lbs
Weight w/ Trailer (Empty):	2700 lbs	2990 lbs	4,210 lbs
Weight w/ Trailer (Working):	7500 lbs	10,670 lbs	15,000 lbs
Fiber Mulch Capacity:	200-250 lbs	300-400 lbs	500-600 lbs
Coverage/ Tank Load (AVG):	5,500 Sq. Ft.	8,800 St. Ft.	13,200 Sq. Ft.
Spray Distance:	Variable up to 75'		
Pump:	2" Rotary Gear		
Power:	22 H.P. Electric Start		
Discharge:	Hose & Cannon		
Hose:	(1) 100' x 1 1/4" Hose		
Nozzles:	(1) Long, (1) Wide		
Agitation:	Paddle		
Fill Wand:	Adjustable Air Gap		



Thick Mulch Slurry



TGMI, Inc.
11074 Ashburn Ave.
Cincinnati, OH 45240

Toll Free: 800-241-8464
Office: 513-825-5444
Fax: 513-825-3393
Web Site: www.mulchers.com